

选型参数表
Selection Table

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机型号 Type Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机型号 Type Type	极数 Pole p
45kW						55kW					
45	8983	32.91	0.84			78	6352	19.04	1.18		
53	7596	27.83	0.99			88	5605	16.80	1.34		
62	6551	24.00	1.15			102	4841	14.51	1.55		
67	6046	22.15	1.24			115	4280	12.83	1.76	R 137	4
78	5197	19.04	1.45			137	3600	10.79	1.90	RF137	4
88	4586	16.80	1.64	R 137	4	170	2906	8.71	2.1		
102	3960	14.51	1.90	RF137	4	195	2532	7.59	2.3		
115	3502	12.83	2.1			232	2128	6.38	2.5		
137	2945	10.79	2.3			287	1718	5.15	2.5		
170	2377	8.71	2.6								
195	2072	7.59	2.8			415	1242	3.57	1.35	RX 157	4
232	1741	6.38	3.1			479	1075	3.09	1.56	RXF157	4
287	1406	5.15	3.1								
75kW						90kW					
96	4220	15.46	0.96			38	17719	38.95	0.95		
110	3685	13.50	1.10			43	15767	34.66	1.07		
129	3125	11.45	1.27			50	13588	29.87	1.25		
148	2732	10.01	1.29			61	11041	24.27	1.43		
175	2309	8.46	1.48	R 107	4	72	9362	20.58	1.53	R 167	4
183	2203	8.07	1.50	RF107	4	79	8521	18.73	1.81	RF167	4
216	1867	6.84	1.71			91	7420	16.31	2.03		
247	1632	5.98	1.75			102	6624	14.56	2.13		
292	1381	5.06	2.0			119	5646	12.41	3.0		
						144	4677	10.28	3.4		
435	968	3.40	1.15			169	3990	8.77	4.0		
493	854	3.00	1.30								
571	737	2.59	1.51	RX 127	4	49	13625	29.95	0.90		
646	652	2.29	1.70	RXF127	4	61	11004	24.19	1.11		
767	549	1.93	2.02			72	9298	20.44	1.20		
						82	8207	18.04	1.21		
438	962	3.38	0.81			95	7115	15.64	1.72		
482	874	3.07	0.89			106	6328	13.91	1.87	R 147	4
561	751	2.64	1.04			123	5454	11.99	2.2	RF147	4
643	654	2.30	1.19	RX 107	4	152	4431	9.74	2.5		
759	555	1.95	1.30	RXF107	4	179	3758	8.26	2.8		
865	487	1.71	1.36			204	3298	7.25	3.0		
1028	410	1.44	1.48			251	2679	5.89	3.3		
						296	2275	5.00	3.6		
55kW						55kW					
29	16984	50.91	1.00			479	1466	3.09	1.15		
33	14989	44.93	1.13			538	1304	2.75	1.29	RX 157	4
38	12984	38.95	1.30			624	1124	2.37	1.49	RXF157	4
43	11563	34.66	1.46			767	915	1.93	1.84		
50	9963	29.87	1.70	R 167	4						
61	8097	24.27	1.96	RF167	4	767	915	1.93	1.21	RX 127	4
72	6866	20.58	2.09			949	740	1.56	1.50	RXF127	4
79	6248	18.73	2.50								
91	5441	16.31	2.76			90kW					
102	4857	14.56	2.90			43	18921	34.66	0.89		
119	4140	12.41	4.09			50	16306	29.87	1.04		
144	3429	10.28	4.66			61	13249	24.27	1.20		
						72	11235	20.58	1.28		
32	15563	46.65	0.8			79	10225	18.73	1.51	R 167	4
37	13441	40.29	0.91			91	8904	16.31	1.69	RF167	4
42	11890	35.64	1.03			102	7947	14.56	1.77		
49	9991	29.95	1.22			119	6775	12.41	2.5		
61	8070	24.19	1.39			144	5612	10.28	2.8		
72	6819	20.44	1.65			169	4788	8.77	3.3		
82	6018	18.04	1.64	R 147	4						
95	5218	15.64	2.3	RF147	4						
106	4640	13.91	2.6								
123	4000	11.99	3.1								
152	3249	9.74	3.8								
204	2419	7.25	3.4								
251	1965	5.89	4.1								

R

选型参数表
Selection Table

输出转速	输出扭矩	传动比	使用系数	机型号	极数	输出转速	输出扭矩	传动比	使用系数	机型号	极数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p
90kW											
72	11158	20.44	1.01								
82	9848	18.04	1.10								
95	8538	15.64	1.43								
106	7593	13.91	1.56	R 147	4						
123	6545	11.99	1.87	RF147	4						
156	5170	9.47	2.1								
179	4509	8.26	2.4								
204	3958	7.25	2.5								
251	3215	5.89	2.7								
296	2729	5.00	3.0								
542	1555	2.75	1.08	RX 157	4						
629	1340	2.37	1.25	RXF157	4						
772	1091	1.93	1.54								
955	882	1.56	1.26	RX 127	4						
				RXF127	4						
110kW											
61	16193	24.27	1.04								
72	13731	20.58	1.23								
91	10882	16.31	1.38	R 167	4						
102	9715	14.56	1.45	RF167	4						
119	8280	12.41	2.04								
144	6859	10.28	2.3								
169	5851	8.77	2.7								
629	1638	2.37	1.03	RX 157	4						
772	1334	1.93	1.26	RXF157	4						
914	1126	1.63	1.49								
132kW											
72	16477	20.58	1.03								
91	13059	16.31	1.15								
102	11657	14.56	1.21	R 167	4						
119	9936	12.41	1.70	RF167	4						
144	8231	10.28	1.94								
169	7022	8.77	2.28								
914	1351	1.63	1.24	RX 157	4						
				RXF157	4						
160kW											
120	11963	12.41	1.41	R 167	4						
145	9910	10.28	1.61	RF167	4						
170	8484	8.77	1.89								

R